

Mini Fuge PLUS

SKU N2631-0017



Product Highlights


- 8-place rotor for 0.2/0.5/1.5/2.0 ml tubes, including screw cap tubes
- 32-place strip rotor for 0.2 ml tubes or strips
- Quick, easy rotor change without the need for tools
- Option of electronic braking or gradual spin stop
- Second lid switch for added safety
- 2-year warranty

Product Applications

Sample

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

STARLAB International GmbH
Neuer Höltingbaum 38
22143 Hamburg
Email: info@starlab.de



General Data

Pack Size	Box
Weight	1.2 kg
Dimensions (W × L)	15 cm ×
Power supply	100 – 240 V, 50/60 Hz
Fuse	0.35 A
Permissible Relative Humidity	>80%
Dimensions (W × H)	15 × 11.6 cm
Permissible ambient temperature	5 to 40 °C
RCF	2000 × g
Packaging Item	Piece
Packaging Unit	Box
Speed	6,000 rpm
Pack Size	1 Box × 1 Piece
Dimensions (W × D × H)	15 cm × 15 cm × 11.6 cm
External width	15 cm

STARLAB reserves the right to make changes at any time and without prior notice. The content and design of this PDF are protected by national and international copyright law and are the property of STARLAB International GmbH. Any duplication, editing, distribution and any kind of use and utilization of this PDF content in electronic systems, online media and / or libraries or similar databases requires the prior consent of STARLAB International GmbH.

STARLAB International GmbH
Neuer Höltigbaum 38
22143 Hamburg
Email: info@starlab.de



More informations about Mini Fuge PLUS

Every bench should have one!

The Mini Fuge PLUS centrifuge is ideal for quick spin down of condensate, vortexed or thawed samples. Microfiltration and cell separation with a speed of 2000 x g is also possible.